

FOQUS™

Model FOCUS is a compact fog cannon for very small rooms up to 25 m². Thanks to its lightweight design, FOQUS is well suited for server rooms, ATM rooms, home offices etc. FOQUS is often used for partial protection as it covers small areas quickly and efficiently.



Up to 5 year warranty

European quality - Danish design. FOQUS comes with a 2 year warranty. Three extra year of warranty for free requires online product registration on protectglobal.com/extra-warranty.

Possibility of 2 angled nozzles

FOQUS comes with a straight nozzle. However it can easily be exchanged with a 30° nozzle.



XTRA⁺ fog fluid

Sturdy, reusable fluid container with XTRA⁺ fog fluid: Extra white and dry fog with extended dissipation time. Quick and easy replacement without fog fluid spillage.

Features:

- Discharges enough fog to cover a room up to 25 m²
- Flexible adjustment between 8 and 25 m² to exactly fit the size of the room
- Pulse function for up to 5 min. (effective maintenance of the fog)
- Compatible with any alarm system including ZOLO GSM Alarm System
- Compatible with IPCard, MultiCard and IntelliBox
- Data log memory possible with IntelliSuite
- Built-in daily, automatic battery test
- Integration with all types of alarm systems
- 100 % silent in standby mode
- Prepared for 2 different angled nozzles

Specifications:

Fog performance, examples: 10 sec. fog + 6 pulse shots 6 sec. fog + 5 min. fog
3 time settings: 8, 16 and 25 m ²
Optional pulse function (can shoot several times)
1,1 l. reusable fluid container included
Enough fluid for 20 discharges in one container
Electronic fluid measurement
Power consumption: 700W
Mains connection: 230V, 50 Hz
Standby consumption after heating up: 55 W (on average)
Standby consumption when heat is disabled: 5-10 W
Heating time from cold: 7 min.
Re-heating time after fog discharge: 0,5-3 min.
Operating temperature (min./max.): 5/80° C.
Input: 5 signals
Output: 3 signals
On/off dipswitches for setting of fog time, signals and heating
Backup of electronics and pump (2 x 12V, 1.2 Ah)
Power backup after power failure: Up to 3 hours
Built-in automatic battery testing
Optical, audible and electrical signals/indicators
Status indicator on PCB
External status indicator
Anti-sabotage, impact-resistant steel casing
Colours available: White
Dimensions: L: 400, W: 240, H: 135 mm
Installation weight: 7 kg

Printing errors excepted. Subject to changes to technical data.



SECURED IN SECONDS